Available online at www.sciencedirect.com
ScienceDirect
Ultrasonics 47 (2007) 140–141
Ultrasonics
www.elsevier.com/locate/ultras

Author Index to Volume 47

Belloncle, V.V., and Rousseau, M.
Empirical rheological model for rough or grooved bonded interfaces 10
Biwa, S., Hiraiwa, S., and Matsumoto, E.
Stiffness evaluation of contacting surfaces by bulk and interface waves 123

Chen, F., and Wilcox, P.D.
The effect of load on guided wave propagation 111
Chen, Q., Zou, X., Cheng, J., and Wu, J.
Application of ultrasound in preparing pathological sections to reduce processing time 78
Cheng, J., see Chen, Q. 78
Cochran, S., see Schmarje, N. 15

de Jong, N., see Emmer, M. 74

Ech-Cherif El-Kettani, M., see Marical, P. 1
Emmer, M., Vos, H.J., van Wamel, A., Goertz, D.E., Versluis, M., and de Jong, N.
Clinical relevance of pressure-dependent scattering at low acoustic pressures 74

Goertz, D.E., see Emmer, M. 74

Hasheminejad, S.M., and Rajabi, M.
Acoustic scattering characteristics of a thick-walled orthotropic cylindrical shell at oblique incidence 32
Hayward, G., see Mulholland, A.J. 102
Hayward, G., see Orr, L.-A. 130
Hiraiwa, S., see Biwa, S. 123

Kimmel, E., see Krasovitski, B. 90
Kirk, K.J., see Schmarje, N. 15
Kislev, H., see Krasovitski, B. 90
Krasovitski, B., Kislev, H., and Kimmel, E.
Modeling photothermal and acoustical induced microbubble generation and growth 90

Lee, J.-J., see Rhee, S.-H. 55
Lee, J.-K., see Rhee, S.-H. 55
Lewin, P.A., see Nowicki, A. 64

Malischewsky, P.G., see Vinh, P.C. 49
Marical, P., Ech-Cherif El-Kettani, M., and Predoi, M.V.
Guided waves in elastic plates with Gaussian section variation: Experimental and numerical results 1
Matsumoto, E., see Biwa, S. 123
Mulholland, A.J., see Orr, L.-A. 130
Mulholland, A.J., O'Leary, R.L., Ramadas, N., Parr, A., Troge, A., Pethrick, R.A., and Hayward, G.
A theoretical analysis of a piezoelectric ultrasound device with an active matching layer 102

Nowicki, A., Trots, I., Lewin, P.A., Secomski, W., and Tymkiewicz, R.
Influence of the ultrasound transducer bandwidth on selection of the complementary Golay bit code length 64

O'Leary, R.L., see Mulholland, A.J. 102
O'Leary, R.L., see Orr, L.-A. 130
Orr, L.-A., Mulholland, A.J., O'Leary, R.L., Parr, A., Pethrick, R.A., and Hayward, G.
Theoretical modelling of frequency dependent elastic loss in composite piezoelectric transducers 130

Parr, A., see Mulholland, A.J. 102
Parr, A., see Orr, L.-A. 130
Pethrick, R.A., see Mulholland, A.J. 102
Pethrick, R.A., see Orr, L.-A. 130
Predoi, M.V., see Marical, P. 1

Rajabi, M., see Hasheminejad, S.M. 32
Ramadas, N., see Mulholland, A.J. 102
Rhee, S.-H., Lee, J.-K., and Lee, J.-J.
The group velocity variation of Lamb wave in fiber reinforced composite plate 55
Rousseau, M., see Belloncle, V.V. 10

Schmarje, N., Kirk, K.J., and Cochran, S.
1–3 Connectivity lithium niobate composites for high temperature operation 15
Secomski, W., see Nowicki, A. 64

Troge, A., see Mulholland, A.J. 102
Trots, I., see Nowicki, A. 64
Tymkiewicz, R., see Nowicki, A. 64

van Wamel, A., see Emmer, M. 74
Versluis, M., see Emmer, M. 74
Vinh, P.C., and Malischewsky, P.G.
An improved approximation of Bergmann's form for the Rayleigh wave velocity 49
Vos, H.J., see Emmer, M. 74

Wang, T.-h., see Zhang, H. 82

doi:10.1016/S0041-624X(07)00111-4

Available online at www.sciencedirect.com
ScienceDirect
Ultrasonics 47 (2007) 140–141
Ultrasonics
www.elsevier.com/locate/ultras

Author Index to Volume 47

Belloncle, V.V., and Rousseau, M.
Empirical rheological model for rough or grooved bonded interfaces 10
Biwa, S., Hiraiwa, S., and Matsumoto, E.
Stiffness evaluation of contacting surfaces by bulk and interface waves 123

Chen, F., and Wilcox, P.D.
The effect of load on guided wave propagation 111
Chen, Q., Zou, X., Cheng, J., and Wu, J.
Application of ultrasound in preparing pathological sections to reduce processing time 78
Cheng, J., see Chen, Q. 78
Cochran, S., see Schmarje, N. 15

de Jong, N., see Emmer, M. 74

Ech-Cherif El-Kettani, M., see Marical, P. 1
Emmer, M., Vos, H.J., van Wamel, A., Goertz, D.E., Versluis, M., and de Jong, N.
Clinical relevance of pressure-dependent scattering at low acoustic pressures 74

Goertz, D.E., see Emmer, M. 74

Hasheminejad, S.M., and Rajabi, M.
Acoustic scattering characteristics of a thick-walled orthotropic cylindrical shell at oblique incidence 32
Hayward, G., see Mulholland, A.J. 102
Hayward, G., see Orr, L.-A. 130
Hiraiwa, S., see Biwa, S. 123

Kimmel, E., see Krasovitski, B. 90
Kirk, K.J., see Schmarje, N. 15
Kislev, H., see Krasovitski, B. 90
Krasovitski, B., Kislev, H., and Kimmel, E.
Modeling photothermal and acoustical induced microbubble generation and growth 90

Lee, J.-J., see Rhee, S.-H. 55
Lee, J.-K., see Rhee, S.-H. 55
Lewin, P.A., see Nowicki, A. 64

Malischewsky, P.G., see Vinh, P.C. 49
Marical, P., Ech-Cherif El-Kettani, M., and Predoi, M.V.
Guided waves in elastic plates with Gaussian section variation: Experimental and numerical results 1
Matsumoto, E., see Biwa, S. 123
Mulholland, A.J., see Orr, L.-A. 130
Mulholland, A.J., O'Leary, R.L., Ramadas, N., Parr, A., Troge, A., Pethrick, R.A., and Hayward, G.
A theoretical analysis of a piezoelectric ultrasound device with an active matching layer 102

Nowicki, A., Trots, I., Lewin, P.A., Secomski, W., and Tymkiewicz, R.
Influence of the ultrasound transducer bandwidth on selection of the complementary Golay bit code length 64

O'Leary, R.L., see Mulholland, A.J. 102
O'Leary, R.L., see Orr, L.-A. 130
Orr, L.-A., Mulholland, A.J., O'Leary, R.L., Parr, A., Pethrick, R.A., and Hayward, G.
Theoretical modelling of frequency dependent elastic loss in composite piezoelectric transducers 130

Parr, A., see Mulholland, A.J. 102
Parr, A., see Orr, L.-A. 130
Pethrick, R.A., see Mulholland, A.J. 102
Pethrick, R.A., see Orr, L.-A. 130
Predoi, M.V., see Marical, P. 1

Rajabi, M., see Hasheminejad, S.M. 32
Ramadas, N., see Mulholland, A.J. 102
Rhee, S.-H., Lee, J.-K., and Lee, J.-J.
The group velocity variation of Lamb wave in fiber reinforced composite plate 55
Rousseau, M., see Belloncle, V.V. 10

Schmarje, N., Kirk, K.J., and Cochran, S.
1–3 Connectivity lithium niobate composites for high temperature operation 15
Secomski, W., see Nowicki, A. 64

Troge, A., see Mulholland, A.J. 102
Trots, I., see Nowicki, A. 64
Tymkiewicz, R., see Nowicki, A. 64

van Wamel, A., see Emmer, M. 74
Versluis, M., see Emmer, M. 74
Vinh, P.C., and Malischewsky, P.G.
An improved approximation of Bergmann's form for the Rayleigh wave velocity 49
Vos, H.J., see Emmer, M. 74

Wang, T.-h., see Zhang, H. 82

doi:10.1016/S0041-624X(07)00111-4

Wen, F., and Yen, C.-Y.
Design and dynamic evaluation for a linear ultrasonic stage using the thin-disc structure actuator 23
Wilcox, P.D., see Chen, F. 111
Wu, J., see Chen, Q. 78

Yen, C.-Y., see Wen, F. 23

Zhang, H., Zhang, S.-y., and Wang, T.-h.
Flexural vibration analyses of piezoelectric ceramic tubes with mass loads in ultrasonic actuators 82
Zhang, S.-y., see Zhang, H. 82
Zou, X., see Chen, Q. 78

Available online at www.sciencedirect.com
ScienceDirect
Ultrasonics 47 (2007) 142
Ultrasonics
www.elsevier.com/locate/ultras

Subject Index to Volume 47

Acoustic characterization, 32
Adiabatic waves, 1
Anisotropic composites, 130

Cell membrane permeability, 78
Clinical relevance, 74
Complementary Golay sequences, 64
Composite materials, 55
Contact interface wave, 123
Contact mechanics, 123
Conversion, 1

Edge-driving actuator, 23
Elastic loss, 130

Flexural vibration, 82
Fluid loading effects, 32
Friction contact, 23

Group velocity, 111
Guided waves, 111

High temperature, 15

Interfacial stiffness, 123

Lamb wave, 55
Lamb waves, 1
Laser, 90
Laser-Doppler measurement, 23
Lithium niobate, 15
Load measurement, 111

Magnetorheological, 102
Matching layer, 102
Modelling, 102

Nanoparticles, 90
Non-destructive testing, 15

Orthotropic cylindrical shell, 32

Pathological sections, 78
Performance evaluation, 23
Phase velocity, 111
Piezoceramic, 23
Piezoelectric ceramic tube, 82
Pressure-dependent threshold behaviour, 74

Rail, 111
Rayleigh wave velocity, 49
Rectified diffusion, 90
Reflection coefficient, 123
Resonance frequency, 82

Surface waves, 32

The best approximation, 49
The method of least squares, 49
Timoshenko beam, 82
Tissue processing, 78
Transducer bandwidth, 64

Ultrasonic actuating stage, 23
Ultrasonic transducer, 102, 130
Ultrasonic transducers, 15
Ultrasound, 78, 90
Ultrasound contrast agents, 74
Ultrasound imaging, 64

Waveguide of varying section, 1

doi:10.1016/S0041-624X(07)00112-6

ULTRASONICS

Volume 47, Numbers 1–4, December 2007

Contents

Regular articles

P. Marical, M. Ech-Cherif El-Kettani and M.V. Predoi
Guided waves in elastic plates with Gaussian section variation: Experimental and numerical results 1

V.V. Belloncle and M. Rousseau
Empirical rheological model for rough or grooved bonded interfaces 10

N. Schmarje, K.J. Kirk and S. Cochran
1–3 Connectivity lithium niobate composites for high temperature operation 15

F. Wen and C.-Y. Yen
Design and dynamic evaluation for a linear ultrasonic stage using the thin-disc structure actuator 23

S.M. Hasheminejad and M. Rajabi
Acoustic scattering characteristics of a thick-walled orthotropic cylindrical shell at oblique incidence 32

P.C. Vinh and P.G. Malischewsky
An improved approximation of Bergmann's form for the Rayleigh wave velocity 49

S.-H. Rhee, J.-K. Lee and J.-J. Lee
The group velocity variation of Lamb wave in fiber reinforced composite plate 55

A. Nowicki, I. Trots, P.A. Lewin, W. Secomski and R. Tymkiewicz
Influence of the ultrasound transducer bandwidth on selection of the complementary Golay bit code length 64

M. Emmer, H.J. Vos, A. van Wamel, D.E. Goertz, M. Versluis and N. de Jong
Clinical relevance of pressure-dependent scattering at low acoustic pressures 74

Q. Chen, X. Zou, J. Cheng and J. Wu
Application of ultrasound in preparing pathological sections to reduce processing time 78

H. Zhang, S.-y. Zhang and T.-h. Wang
Flexural vibration analyses of piezoelectric ceramic tubes with mass loads in ultrasonic actuators 82

B. Krasovitski, H. Kislev and E. Kimmel
Modeling photothermal and acoustical induced microbubble generation and growth 90

A.J. Mulholland, R.L. O'Leary, N. Ramadas, A. Parr, A. Troge, R.A. Pethrick and G. Hayward
A theoretical analysis of a piezoelectric ultrasound device with an active matching layer 102

F. Chen and P.D. Wilcox
The effect of load on guided wave propagation 111

S. Biwa, S. Hiraiwa and E. Matsumoto
Stiffness evaluation of contacting surfaces by bulk and interface waves 123

L.-A. Orr, A.J. Mulholland, R.L. O'Leary, A. Parr, R.A. Pethrick and G. Hayward
Theoretical modelling of frequency dependent elastic loss in composite piezoelectric transducers 130

Calendar 138

Author Index to Volume 47 140

Subject Index to Volume 47 142

0041-624X(200712)47:1-4;1-1